(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 4 August 2005 (04.08.2005)

PCT

(10) International Publication Number WO 2005/070491 A3

- (51) International Patent Classification⁷: A61M 25/01, A61B 18/00
- (21) International Application Number:

PCT/AU2005/000058

- (22) International Filing Date: 20 January 2005 (20.01.2005)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/539,519


26 January 2004 (26.01.2004) US

- (71) Applicant (for all designated States except US): CATHRX PTY LTD [AU/AU]; Room G11, National Innovation Centre, Australian Technology Park, Eveleigh, NSW 1430 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): BOOTH, Norman [AU/AU]; 24 Tusculum Court, Wattle Grove, NSW 2173 (AU).

- (74) Agent: F B RICE & CO; 605 Darling Street, Balmain, NSW 2041 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A CATHETER ASSEMBLY WITH AN ADJUSTABLE LOOP



(57) Abstract: A catheter assembly (10) including at least one introducer (12) defining passage (18) receiving elongate tubular member (20) having proximal end, distal end and lumen extending between. Elongate shape imparting element (32) received in lumen and imparting predetermined shape (26) to distal end of tubular member (20) when distal end of tubular member is extended beyond distal end of introducer (12). Distal end of shape imparting element (32) extends from lumen of tubular member (20) and is anchored proximally of distal end of introducer (12).

WO 2005/070491 A3



Published:

with international search report

(88) Date of publication of the international search report: 15 September 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.